

Lödal

EVO Series

ECO Series

Front Loader

Bucket Loader

In The News


Sales & Service

Plant Tour

Contact Us

EVO Series

EVO T-28 Route Builder



Specifications:

Vehicle Weight Rating

G.V.W. 52,000 lbs.

Vehicle Empty Weights (approx.)

Front axle - 16,500 lbs.

Rear axle -- 11,000 lbs.

Total ----- 27,500 lbs.

Front Drive Axle & Springs

Side Loading Hopper (Midships)

1.65 cu. yd. cap. (330 gal.) Straight
Down Sides

32" Deep X 50" Wide X 48" Long

Loading Height - 34" Running Board

48" - from Ground

20,000 lbs. cap. Dana
SD66-1X
axle Ratios: 6:21
Front Springs - 12,000 lbs.
cap. ea. @ pad, 4" X 52" -
10 Leaf
Front Shock Absorbers
Integral Pinion Mt'd 1:1
Drop box

Independent Rear Suspension

Tandem axle w/equalizer
Beam
Dana Wheel Ends - Non-
driving

Front & Rear Tires & Wheels

Front : 15.0 X 22.5 18 Ply
Goodyear G286 Radials
Rear: 15.0 X 22.5 18 Ply
Goodyear G286 Radials
Pressed Disc Wheels -
12.25 Rim - 10 Stud

Refuse Body - 25 cu. yd. cap.

Tailgate - Top Hinged, Self
Locking
Tailgate Hyd. Cyls. - 4" D X
23.25" Stroke
Integrated Body, Hopper &
Forward Frame

10" Fold-up Bang Board - Left Side
Hopper

Side Running Boards

Within width of vehicle Low Step - 9"
to 11" height 12" W X 60" L Plus 17"
Platform

Skid Resistant Open Tread

Compactor Ram & Load Ejector

130,000 lb. Compaction Force @
3000 P.S.I.

2 Hyd. Cyls. - 3 Stage telescopic 5.25"
D. 1st Stage, 4.25" D. 2nd Stage,
3.25" D 3rd Stage

Compactor Ram - 50" Wide X 32"

Deep with 72" Long Rigid Top Cover

Hydraulic System (3,000 P.S.I.)

Pump - Gear Type, 30 GPM @ 1400
RPM

Pump Drive - Direct off Engine
Crankshaft

Direct PTO Shaft - Spicer 1350

Hyd. Res. - 48 gal. w/Sight Gauge

Hyd. Control valve - 2 Spool (Air
Oper. Compact) Push Button hyd.

Compaction Control & Emergency

Stop Button on each side of hopper &
inside cab

Manual Hyd. Control Levers each side
of Hopper

Also see: [Standard Equipment](#) & [Popular Options](#)

